

# ZAHRA INDUSTRIES L.L.C.

P.O. Box No.: 376995, Dubai, U.A.E., Tel No.: +9714-3242455, Fax: +9714-3242455  
E-mail: [zahraindustry@gmail.com](mailto:zahraindustry@gmail.com), Web: [www.zaratapes.com](http://www.zaratapes.com)

## MASKING TAPE

### TECHNICAL PRODUCT INFORMATION

### ASTM Standard or GB standard

#### Description

General purpose Masking tape. ,tapeCrepe paper as backing and coating with Natural rubber

#### Adhesive

- ▶ Coated with Natural rubber
- ▶ Resist 80c
- ▶ Color: Natural whitr or Beign or Yellow color

#### Carrier

- ▶ crepe Masking paper

#### Applications

- ▶ Indoor painting,
- ▶ Light packaging,
- ▶ Labeling and bundling.
- ▶ UV Resistant,
- ▶ Clean release after use,
- ▶ Easy Tear,
- ▶ Able to stand extreme temperature,
- ▶ Usable on all surfaces.

#### Technical Details

- ▶ Total thickness ----- 0.15MM+-0.01MM
- ▶ Adhesive to steel----- >20 OZ/IN
- ▶ Tensile Strength ----->20N/10MM
- ▶ Rolling ball tack -----8# (Ball no.)
- ▶ Elongation at break -----8-10%
- ▶ Service temperature range ----- 5°C ---- + 80°C

#### Application

Temperature: between 0°C and + 80°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23 °C.

#### Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature between 0°C and 50°C. Stored under these conditions shelf life will be a minimum of 12 months.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications..